Safety Data Sheet

A206 OUTTM Silicone Mold Release



Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

1. IDENTIFICATION

Stoner Incorporated 1070 Robert Fulton Hwy. Quarryville, PA 17566 1-800-227-5538 Product Name: OUT™ Silicone Mold Release

Product Code: A206

Product Use: Mold Release

24-hour emergency phone: 1-800-424-9300 [CHEMTREC]

2. HAZARD IDENTIFICATION

POTENTIAL HEALTH EFFECTS

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols







GHS Classification Flammable Aerosol Category 1

Gases under pressure - Liquified Gas Aspiration Hazard Category 1 Skin Corrosion/Irritation Category 2

Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3

Signal Word Danger

Hazard Statements Extremely flammable aerosol.

Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways.

Causes skin irritation.

May cause drowsiness or dizziness.

Precautionary Statements

Prevention Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 - Wash thoroughly after handling. Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Response P301+P310 - If swallowed: Immediately call a poison center, doctor or medical center.

P302+P352 - If on skin: Wash with plenty of soap and water.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P312 - Call a poison center, doctor or medical center if you feel unwell.

P321 - Specific treatment (see on this SDS).

Do NOT induce vomiting.

If skin irritation occurs: Get medical advice/attention.

Storage Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight. Store in a well-ventilated place.

Protect from sunlight. Do no expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous

wastes.

3. COMPOSITION/INFORMATION ON INGREDIENTS

 COMPONENT
 CAS #
 Percent

 Hydrocarbon propellant
 68476-86-8
 60 - 80

 Aliphatic hydrocarbons
 142-82-5
 1-20

HMIS® III* HAZARDOUS WARNINGS:

Health: 1 Flammability: 4 Physical: 0 Personal See Section 8

Protective Equipment:

4. FIRST AID MEASURES

Eyes: Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there

is visual difficulty, seek medical attention.

Skin Contact: For liquid contact, treat for frostbite if necessary. In case of contact, immediately wash contaminated area with plenty of water for

at least 15 minutes. Seek medical attention if symptoms persist. Wash clothing before reuse.

Ingestion: Do not induce vomiting. Aspiration into the lungs can cause serious damage. If vomiting occurs spontaneously, keep head below

hips to prevent aspiration of liquid into lungs. Contact a physician, medical facility, or poison control center immediately.

Inhalation: Remove affected person to fresh air. No first aid should be needed. No specific treatment is necessary since this material is not

likely to be hazardous by inhalation.

NOTES TO PHYSICIAN:

This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used only in situations of emergency life support. This material is an aspiration hazard. Aspiration during swallowing or vomiting may severely damage the lungs. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin; lung (for example, asthma-like conditions); kidney; central nervous system; auditory system; arrhythmias (irregular heartbeats);

5. FIRE FIGHTING MEASURES

Fire and/or Explosion Hazards: This product contains a component(s) that is considered an extremely flammable gas(es), which has vapors that

are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. This product contains a component(s) that is considered a flammable liquid, which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point."Empty" containers retain product residue and can be

dangerous.

Fire Fighting Instructions: Use CO2, foam or dry chemical. Fire fighters should wear normal protective equipment and positive-pressure self-

contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Ventilate contaminated area. Avoid run-off into storm sewers and ditches which may lead to natural waterways. If runoff occurs, notify authorities as required. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly.

7. HANDLING AND STORAGE

Handling: This material can be harmful or irritating. Use with adequate ventilation. Normal precautions common to safe manufacturing practice

should be followed in handling and storage. Avoid prolonged or repeated breathing of vapor. Avoid prolonged or repeated contact with skin. Do not use near ignition sources. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame,

sparks, static electricity, or other sources of ignition; they may explode and cause injury or death.

Storage: Do not store at temperatures above 122 degrees F. Store away from incompatible materials such as materials that support combustion (oxidizing materials) and corrosive materials (strong acids or bases). Store in a cool, dry, well ventilated area away from all sources of

ignition. Empty container may contain residues which are hazardous. Normal precautions common to safe manufacturing practice should

be followed in handling and storage.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Ventilation is required to maintain operator exposure below published exposure limits. Ventilation should be adequate to prevent exposures above the limits indicated below in this section of the SDS (from known, suspected or apparent adverse

prevent exposures above the finite indicated below in this section of the 5D5 (from known, suspected of apparent adverse

effects)

Eye Protection: Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as

chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or

airborne material. Have an eye wash station available.

Skin Protection: The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with

skin.

Respiratory Protection: A supplied air respirator should be used if ventilation is not sufficient to maintain exposure limits. Use NIOSH approved

respirator where there is likelihood of inhalation of the product mist, spray or aerosol.

COMPONENTCAS #
Hydrocarbon propellantACGIH TLV
68476-86-8OSHA PEL
1000ppmOTHER
Not establishedAliphatic hydrocarbons142-82-5400 ppm TWANot establishedNot established

Stoner Incorporated A206 PAGE 2

^{*} See www.paint.org/hmis or call the ACA at 1 (202) 462-6272 for more information on this current rating system.

9. PHYSICAL AND CHEMICAL PROPERTIES

Not applicable Physical State: Aerosol can Lower Flammability Limit (%): Clear Colorless Appearance: Upper Flammability Limit (%): Not applicable Odor: Petroleum solvent 62.00 Vapor Pressure (PSIG @ 70°F): Vapor Density [air = 1]: Odor Threshold: Mild >1 pH: Not applicable Relative Density (H2O=1): 0.6

Melting/Freezing Point (°F): No data available Solubility in Water: Negligible; 0-1% Boiling Point (°F): No data available Partial Coefficient: n- No data available

octanol/water:

Flash Point (°F PMCC): Not applicable Autoignition Temperature (°F): 474

Evaporation Rate: Not determined Decomposition Temperature (°F): No data available Flammability (solid, gas): No data available Viscosity, dynamic (cSt): No data available

Percent VOCs (%): 80 - 100

10. STABILITY AND REACTION

Chemical Stability: Stable.

Conditions to Avoid: Avoid contact with: Strong oxidizing agents. Ignition sources such as open flames, sparks, static discharges or glowing

metal surfaces

Decomposition Products: Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. Various hydrocarbons.

When heated to temperatures above 150°C in the presence of air, one of the ingredients in this product can form formaldehyde vapors. Formaldehyde vapor is harmful by inhalation; irritating to eyes; sensitizer to the respiratory

system; an acute toxicant and a potential cancer hazard at concentrations greater than 0.75 ppm.

11. TOXICOLOGICAL INFORMATION

Reproductive & No data available.

Developmental Toxicity:

IARC Carcinogen Designation: No data available

Ingredient CAS # Toxicological Data

Aliphatic hydrocarbons 142-82-5 INHALATION LC50 Rat 103 GM/M3

12. ECOLOGICAL INFORMATION

Ecological Toxicity: No data available Mobility: No data available

Ingredient CAS # Toxicological Data

Aliphatic hydrocarbons 142-82-5 Aquatic LC50 (24h) Fish = 4 mg/L

48HR EC50 Daphnia = 1.5 mg/L 96HR EC50 Algae = 3.7 mg/L

No data available

13. DISPOSAL CONSIDERATIONS

Disposal: Dispose according to Federal, State and local regulations.

14. TRANSPORTATION INFORMATION

Agency	UN Number	Proper Shipping name	Hazard Class	Packing Group
DOT	UN1950	Aerosols, Flammable†	2.1	Not applicable
IATA	ID8000	Consumer Commodity†	9	Not applicable
IMDG	UN1950	Aerosols, Flammable†	2.1	Not applicable

^{† &}quot;Limited Quantities" may be applicable for this transportation mode.

15. REGULATORY INFORMATION

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:

COMPONENT CAS # % BY WEIGHT Regulatory Body
No components listed in this section. SARA Section 313

Toxic Substances Control Act

All components of this product are listed on the TSCA inventory.

California Prop 65

This product contains no California Proposition 65 ingredients that cause cancer, birth defects or other reproductive harm.

16. OTHER INFORMATION

Other Information: SDS Prepared by L. Dean Swartz, SDS Coordinator

Version Date: 01/09/18

This information contained in this SDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.