

## Safety Data Sheet

### A595 Heavy Duty Mold Cleaner

# Stoner

Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

#### 1. IDENTIFICATION

Stoner Incorporated  
1070 Robert Fulton Hwy.  
Quarryville, PA 17566  
1-800-227-5538

Product Name: Heavy Duty Mold Cleaner  
Product Code: A595  
Product Use: No data available  
24-hour emergency phone: 1-800-424-9300 [CHEMTREC]

#### 2. HAZARD IDENTIFICATION

##### POTENTIAL HEALTH EFFECTS

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols



##### GHS Classification

Gases under pressure - Refrigerated Liquified Gas  
Flammable Aerosol Category 2  
Skin Corrosion/Irritation Category 2  
Serious Eye Damage/Eye Irritation Category 2A  
Carcinogenicity Category 2  
Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3

##### Signal Word

Warning

##### Hazard Statements

Flammable aerosol.  
Contains refrigerated gas; may cause cryogenic burns or injury.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Suspected of causing cancer.

##### Precautionary Statements

###### Prevention

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat/sparks/open flames/hot surfaces. – No smoking.  
Do not spray on an open flame or other ignition source.  
Pressurized container: Do not pierce or burn, even after use.  
Avoid breathing dust/fume/gas/mist/vapours/spray.  
P264 - Wash thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves/protective clothing/eye protection/face protection.  
Wear cold insulating gloves/face shield/eye protection.

###### Response

P302+P352 - If on skin: Wash with plenty of soap and water.  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
IF exposed or concerned: Get medical advice/attention.  
P312 - Call a poison center, doctor or medical center if you feel unwell.  
Get immediate medical advice/attention.  
P321 - Specific treatment (see on this SDS).  
If skin irritation occurs: Get medical advice/attention.  
Thaw frosted parts with lukewarm water. Do no rub affected area.  
If eye irritation persists: Get medical advice/attention.

##### Storage

Store in a well-ventilated place.  
Store in a well-ventilated place. Keep container tightly closed.  
Store locked up.  
Protect from sunlight. Do no expose to temperatures exceeding 50°C/ 122°F.

##### Disposal

Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

<b>COMPONENT</b>	<b>CAS #</b>	<b>Percent</b>
Aliphatic hydrocarbons	142-82-5	40 - 60
Xylene	1330-20-7	10 - 30
2-propanone	67-64-1	1-20
Propellant	124-38-9	1-20
Ethyl benzene	100-41-4	3 - 7
Cumene	98-82-8	0.01- 0.3

#### HMIS® III\* HAZARDOUS WARNINGS:

Health: 2	Flammability: 2	Physical: 0	Personal Protective Equipment:	See Section 8
-----------	-----------------	-------------	--------------------------------	---------------

\* See [www.paint.org/hmis](http://www.paint.org/hmis) or call the ACA at 1 (202) 462-6272 for more information on this current rating system.

### 4. FIRST AID MEASURES

Eyes:	Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there is visual difficulty, seek medical attention.
Skin Contact:	In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. Seek medical attention if symptoms persist. Wash clothing before reuse. For liquid contact, treat for frostbite if necessary.
Ingestion:	Do not induce vomiting. Aspiration into the lungs can cause serious damage. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs. Contact a physician, medical facility, or poison control center immediately.
Inhalation:	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep the victim warm and quiet. Seek immediate medical attention. Continue your efforts until help arrives or the victim starts to breathe on his own. Do not leave victim alone.

#### NOTES TO PHYSICIAN:

This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used only in situations of emergency life support. This material is an aspiration hazard. Aspiration during swallowing or vomiting may severely damage the lungs. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin; lung (for example, asthma-like conditions); kidney; central nervous system; auditory system; arrhythmias (irregular heartbeats); liver; blood forming system;

### 5. FIRE FIGHTING MEASURES

Fire and/or Explosion Hazards:	This product contains a component(s) that is considered a flammable liquid, which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. "Empty" containers retain product residue and can be dangerous. Containers may rupture or explode under fire conditions.
Fire Fighting Instructions:	Use CO <sub>2</sub> , foam or dry chemical. Water is generally not effective and may spread fire; however, water spray may be used from a safe distance to cool closed containers and protect surrounding area.

### 6. ACCIDENTAL RELEASE MEASURES

#### STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Ventilate contaminated area. Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Avoid run-off into storm sewers and ditches which may lead to natural waterways. If runoff occurs, notify authorities as required. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly.

### 7. HANDLING AND STORAGE

Handling:	Do not use near ignition sources. Normal precautions common to safe manufacturing practice should be followed in handling and storage. This material can be harmful or irritating. Avoid prolonged or repeated contact with skin. Avoid prolonged or repeated breathing of vapor. Use with adequate ventilation. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode and cause injury or death. If ventilation is not sufficient, wear proper respiratory equipment. Do not store containers in excessive heat or direct sunlight. Protect container against physical damage.
Storage:	Store in a cool, dry, well ventilated area away from all sources of ignition. Empty container may contain residues which are hazardous. Normal precautions common to safe manufacturing practice should be followed in handling and storage. Keep away from heat, sparks and flame. Do not store at temperatures above 122 degrees F.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls:	Ventilation should be adequate to prevent exposures above the limits indicated below in this section of the SDS (from known, suspected or apparent adverse effects). Local exhaust should be used in areas where exposure limits may be exceeded.
Eye Protection:	Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Have an eye wash station available.
Skin Protection:	The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with skin.
Respiratory Protection:	A supplied air respirator should be used if ventilation is not sufficient to maintain exposure limits. Use NIOSH approved respirator where there is likelihood of inhalation of the product mist, spray or aerosol.

<u>COMPONENT</u>	<u>CAS #</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER</u>
Aliphatic hydrocarbons	142-82-5	400 ppm TWA	Not established	Not established
Xylene	1330-20-7	150 PPM STEL; 651 MG/M3 STEL	Not established	100ppm
2-propanone	67-64-1	500 ppm TWA	Not established	Not established
Propellant	124-38-9	5000 ppm	5000 ppm	Not established
Ethyl benzene	100-41-4	20 ppm TWA	100ppm TWA	100ppm 10 hr-TWA (NIOSH)
Cumene	98-82-8	Not established	50ppm TWA	Not established

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Aerosol can	Lower Flammability Limit (%):	Not applicable
Appearance:	Clear Colorless	Upper Flammability Limit (%):	Not applicable
Odor:	Light Hydrocarbon Aromatic Sweet odor	Vapor Pressure (PSIG @ 70°F):	No data available
Odor Threshold:	Mild	Vapor Density [air = 1]:	>1
pH:	Not applicable	Relative Density (H2O=1):	0.82
Melting/Freezing Point (°F):	No data available	Solubility in Water:	Negligible; 0-1% Insoluble
Boiling Point (°F):	No data available	Partial Coefficient: n-octanol/water:	0.2
Flash Point (°F PMCC):	Not applicable	Autoignition Temperature (°F):	474
Evaporation Rate:	Not determined	Decomposition Temperature (°F):	No data available
Flammability (solid, gas):	No data available	Viscosity, dynamic (cSt):	0.3
Percent VOCs (%):	60 - 80		

## 10. STABILITY AND REACTION

Chemical Stability:	Stable.
Conditions to Avoid:	Avoid contact with: Ignition sources such as open flames, sparks, static discharges or glowing metal surfaces. Strong oxidizing agents. Acids. Alkali. Alkaline earth metals. Metal acetylides. Chromium. Titanium above 550° C. Uranium above 750° C.
Decomposition Products:	Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. Various hydrocarbons. Carbon Monoxide. Oxygen.

## 11. TOXICOLOGICAL INFORMATION

Reproductive & Developmental Toxicity:	No data available.
IARC Carcinogen Designation:	No data available

<u>Ingredient</u>	<u>CAS #</u>	<u>Toxicological Data</u>
Aliphatic hydrocarbons	142-82-5	Inhalation LC50 Rat 103 GM/M3
Xylenes	1330-20-7	Dermal LD50 Rabbit 1700 mg/kg Oral LD50 Mouse 2119 mg/kg Oral LD50 Rat 4300 mg/kg
2-propanone	67-64-1	Inhalation LC50 Rat 5000 ppm Dermal LD50 GUINEA PIG 9400 UL/KG Oral LD50 Mouse 3 GM/KG
Propellant	124-38-9	Inhalation LC50 Rat 50100 MG/M3 Inhalation LC50 Mouse 200000 ppm Inhalation LC50 Mouse 361 GM/M3 Inhalation LC50 Rat 470000 ppm
Ethyl benzene	100-41-4	Dermal LD50 Rabbit 5000 mg/kg Inhalation LC50 Mouse 35500 MG/M3

## 12. ECOLOGICAL INFORMATION

Ecological Toxicity:	No data available
Mobility:	No data available
Degradability:	No data available.

<b>Ingredient</b>	<b>CAS #</b>	<b>Toxicological Data</b>
Aliphatic hydrocarbons	142-82-5	Aquatic LC50 (24h) Fish = 4 mg/L 48HR EC50 Daphnia = 1.5 mg/L 96HR EC50 Algae = 3.7 mg/L No data available
Xylene	1330-20-7	Aquatic LC50 (96h) MINNOW 24 - 30 mg/L Aquatic LC50 (24h) Daphnia 100 - 1000 mg/L Code:
2-propanone	67-64-1	Aquatic LC50 (48h) Rainbow Trout = 6100 mg/L 48HR EC50 Daphnia = 7630 mg/L 96H EC50 PSEUDOKIRCHNERIELLA SUBCAPITATA 0.0209MG/
Propellant	124-38-9	Aquatic LC50 (96h) Rainbow Trout 35 mg/L No data available No data available
Ethyl benzene	100-41-4	Aquatic LC50 (96h) Rainbow Trout = 8.4 mg/L 48HR EC50 Daphnia = 9.55 mg/L 72HR EC50 Algae 4.9 mg/L

### 13. DISPOSAL CONSIDERATIONS

Disposal : Dispose according to Federal, State and local regulations.

### 14. TRANSPORTATION INFORMATION

<b>Agency</b>	<b>UN Number</b>	<b>Proper Shipping name</b>	<b>Hazard Class</b>	<b>Packing Group</b>
DOT		Not regulated by agency†	ORM-D	Not applicable
IATA	ID8000	Consumer Commodity†	9	Not applicable
IMDG	UN1950	Aerosols, Flammable†	2.1	Not applicable

† "Limited Quantities" may be applicable for this transportation mode.

### 15. REGULATORY INFORMATION

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:

<b>COMPONENT</b>	<b>CAS #</b>	<b>% BY WEIGHT</b>	<b>Regulatory Body</b>
Xylene	1330-20-7	10 - 30	SARA Section 313
Ethyl benzene	100-41-4	3 - 7	SARA Section 313

#### Toxic Substances Control Act

All components of this product are listed on the TSCA inventory.

#### California Prop 65



**WARNING:** This product can expose you to Cumene, Ethyl benzene, which is(are) known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### 16. OTHER INFORMATION

Other Information : SDS Prepared by L. Dean Swartz, SDS Coordinator

Version Date: 03/09/20

This information contained in this SDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.