

Flexible drum heaters can save time by heating stored viscous fluid to a pourable temperature. The heater is built to be tough, long lasting, and resistant to chemicals. Because few materials stick to its silicone rubber with fiberglass reinforced construction, it is easy to clean. The heater comes with a 6-foot cord and plug (120V only). When not in use, it rolls for convenient storage. The total wattage (number of heaters) and the material being heated inside of the drum must be considered when determining the actual temperature to which that specific material can be heated.



Specifications & Features:

- Maximum operating temperature of 425°F.
- Power cord is 6-foot long, SJO Type 16/3 complete with three-prong plug for 120 VAC models. Plugs are not included on 240 VAC models.
- Surface grounded electrically with internal metal screen.
- 1250 volts dielectric tested.
- Vulcanized silicone rubber construction resistant to moisture, ozone, fungus and radiation and chemicals.
- Easy to clean.
- UL and CSA approved.
- Lead time: stock to 2 weeks.

Drum Size	Drum Diameter	Heater Width	Heater Length	Watts	Thermostat Range	Part Number		Price
						120V	240V	
5 Gal.	11.5	3"	31"	300	50-425 F	DHR00150	DHR01010	167.05
15 Gal.	13.5	3"	38"	500	50-425 F	DHR00110	DHR00130	189.15
30 Gal.	18	3"	52"	750	50-425 F	DHR00070	DHR00090	196.95
55 Gal.	22.5	3"	64"	1000	50-425 F	DHR00020	DHR00040	203.40
5 Gal.	11.5	3"	31"	300	No	DHR00140	DHR01041	127.85
15 Gal.	13.5	3"	38"	500	No	DHR00100	DHR00120	149.95
30 Gal.	18	3"	52"	750	No	DHR00060	DHR00080	157.75
55 Gal.	22.5	3"	64"	1000	No	DHR00010	DHR00030	164.20
5 Gal.	11.5	4"	31"	550	50-425 F	DHR01014	DHR01018	282.40
15 Gal.	13.5	4"	38"	700	50-425 F	DHR01013	DHR01017	296.40
30 Gal.	18	4"	52"	1000	50-425 F	DHR01012	DHR01016	313.90
55 Gal.	22.5	4"	64"	1500	50-425 F	DHR00050	DHR00055	337.65
5 Gal.	11.5	9.5"	31"	1000	70-190 F	DHR01023	DHR01047	329.05
15 Gal.	13.5	9.5"	38"	1000	70-190 F	DHR01024	DHR01046	403.45
55 Gal.	22.5	9.5"	64"	1500	70-190 F	DHR01025	DHR01045	602.00