

General Service Hose

GST® II General Service Air & Water Hose For Use with Hose Clamps

An economical and versatile general purpose hose, which is excellent for air and water service. The EPDM tube and cover resists heat, sunlight, ozone and weathering. The GST II hose exceeds RMS class C medium oil resistance requirements. Suitable for applications such as oil mist lubricating air lines, but NOT suitable for the transfer of petroleum products. Closely plied reinforcement of high tensile textile cord provides excellent coupling retention and kink resistance.

Tube: Black EPDM
Cover: EPDM - Red
Reinforcement: Multiple Textile Spirals
Maximum PSI: 300 PSI
Temperature Range: -40° F to +212° F



Part Number	Hose I.D.	Hose O.D.	Minimum Bend Radius	Approx. Full Reel Qty.	Approx. WT/100'	Price Per Foot	
						Cut Length	Full Reel
7092-25300	1/4	.550	3.3	750	12	.47	.45
7092-38300	3/8	.688	4.0	700	17	.59	.56
7092-50304	1/2	.875	5.0	500	25	.79	.75
7092-75304	3/4	1.156	6.0	400	37	.93	.88
7092-100304	1	1.438	8.0	300	53	1.66	1.58
7092-125204	1-1/4	1.781	9.0	300	77	2.93	2.78
7092-150204	1-1/2	2.031	10.0	300	86	3.54	3.36

Worm Gear Hose Clamps

Ideal 57 Series Tridon 611 Series

Band & Housing: 1/2" design, 201/301 stainless steel.
Screw: 5/16" hex-head, plated carbon steel.



1/2" Band Clamps			
Part Number	SAE Sizes	Diameter Range	10 Pieces per Box
			Per Box
5706	6	3/8" - 7/8"	4.30
5708	8	7/16" - 1"	4.30
5710	10	1/2" - 1-1/16"	4.30
5712	12	1/2" - 1-1/4"	4.35
5716	16	1-1/16" - 1-1/2"	4.35
5720	20	3/4" - 1-3/4"	4.40
5724	24	1" - 2"	4.40
5728	28	1-1/4" - 2-1/4"	4.45
5732	32	1-1/2" - 2-1/2"	4.45